



# Product Data Sheet

## Product Description

Product Name:	ProFlush WBD-260
Chemical Name:	Cementing pre-flush
Company Name:	ARC Products Inc
Address:	4010 La Reunion Parkway Suite 160 Dallas, TX 75212
Telephone Number:	(214) 638-2468

## Product Applications

ProFlush WBD-260 is a powdered pre-flush that was designed to simultaneously wet formation surfaces and help remove water based drilling muds as preparation for the next step of the cementing process. WBD-260 disperses quickly into water and does not clump or gel, causing no problems during pumping.

ProFlush WBD-260 is pumped ahead of the cement to separate it from water based drilling muds. When pumped ahead of the cement ProFlush WBD-260 will leave downhole surfaces water wet and remove drilling mud residue, which can result in an improvement in quality of the bond between cement, casing and formation.

ProFlush WBD-260 should be compatible with all water based muds and cement slurries but if uncertain test for compatibility before using the product. ProFlush WBD-260 should be compatible with nonionic and anionic additives.

## Typical Properties

Appearance	Tan powder
pH, (5%w/w in DI water)	8.0 - 10.0
Density (lbs/ft <sup>3</sup> )	51 - 59
Specific gravity	2.01

## Storage and Handling

**Storage** Make sure that partial bags are tightly sealed because the product is slightly hygroscopic.

**Handling** Use appropriate personal protective equipment when working with ProFlush WBD-260. Do not get into eyes, on skin, ingest or inhale dust generated during the use of the product. Try to prevent the generation of dust during use of the product. Make sure that proper ventilation and eye washes/safety showers are present in the immediate work area. Do not flush product into the sewer system.

Date: 04/24/2023  
Revision: New